N
NOTES:
1. THE UNDERPAVEMENT STORMWATER MANAGEMENT IS NECESSARY TO ACHIEVE THE 5:1 LOADING RATIO OF IMPERVIOUS AREA TO INFILTRATION AREA.
2. INFILTRATION BASINS FOR THE BLUE AND GREEN AREAS ARE ASSUMED TO BE UNDER PAVEMENT IN THE AREA OF THE OUTDOOR WATER PARK.
0
300'
600'
1": 300'
DA--A
DA-B
DA-D
STORMWATER BMP (TYP.)
TRENCH STORMWATER DIFFUSER (TYP.)
Pennoni Associates Inc.
Consulting Engineers
Pennoni
One Drexel Plaza
3001 Market Street
Philadelphia, PA
KALAHARI RESORT – BMP EXHIBIT
TOBYHANNA TOWNSHIP
MONROE COUNTY, PENNSYLVANIA
ARCHITECTURAL DESIGN CONSULTANTS, INC.
30 WISCONSIN DELLS PARKWAY PO BOX 580
LAKE DELTON, WI 53940
SCALE: 1"=500'
DATE: 10/18/2012
DWN BY: AD
REV.: KAM
REV. BY:
DWG #:
JOB #: ADCI 1201
SHEET: